

**SV-CLCD70B/  
SV-CLCD56B - KITS**



*This collision avoidance system supports up to two cameras so whether you have a single blind spot or multiple you can get full coverage. By day, enjoy images in brilliant color; and even in low illuminated conditions, you see the clearest image possible with the camera's 18 infrared illuminators.*

**SPECIFICATIONS**

**SV-LCD70B / SV-LCD56B Monitors**

LCD Profile Screen Ratio 5.6-inch, 7-inch	4:3, 16:9
Video System	NTSC standard signal
Auto Dimmer	Yes
OSD Controls	Color, brightness, contrast, volume, languages <i>(English, French, German, Spanish, Portuguese, Indian)</i>
Impact Rating	4G
Sync System	Internal
Power Requirement	12 VDC
Power Consumption	5W
Operating Temperature	-22°F ~ 149°F (-15°C ~ -65°C)
Dimensions (w x h x d) 5.6-inch 7-inch	6.5 in. x 4.5 in. x 1.1 in. (165 mm x 115 mm x 29 mm) 7.9 in. x 4.5 in. x 1.1 in. (200 mm x 115 mm x 29 mm)
Weight 5.6-inch, 7-inch	0.75 lb. (0.34 kg), 0.88 lb. (0.40 kg)

**SV-625B-KIT Camera**

Image Sensor	Color CCD
Signal Format	NTSC
Picture Elements	270,000 pixels
Field of View	110°
Lens Focal Length	2.6 mm
Sync System	Internal
Horizontal Resolution	420 TV lines
Minimum Illumination	0 Lux (IR on), 1 Lux (IR off)
Impact Rating	8G
Power Requirement	12 VDC
Operating Temperature	-22°F ~ 149°F (-30°C ~ 65°C)
Dimensions (w x h x d)	2.8 in. x 3.2 in. x 2.3 in. (73 mm x 82 mm x 58 mm)
Weight	0.84 lb. (0.38 kg)

The compact flat screen monitor takes minimal space while providing you with a clear view of your most vulnerable areas. Whether you prefer the monitor to display as the vehicle is engaged in reverse gear or automatically activate when the vehicle starts, you can choose the option best suited to your driving needs. With the camera's built-in microphone, you can hear as well as see what's behind you.

**Features**

- Available with a compact 5.6-inch monitor or 7-inch wide screen format for optimal viewing
- The automatic day/night sensor ensures excellent picture quality even in low light conditions
- System can automatically activate when the vehicle starts or is placed in reverse and supports single or multiple cameras



**Single Camera  
Control Box**



**Dual Camera  
Control Box**



## Optional Accessories



### LCD RAM Mount/Swivel Pedestal

Safety Vision offers a variety of mounting options for our monitors. The ram mount is ideal for heavy duty operations and the swivel pedestal allows for flexible viewing angles.



### Camera Cage/Cables

Safety Vision offers a wide range of cable types and lengths from 16 feet to over 100 feet. Sectional cables provide ease of installation and repair. Heavy duty operations benefit from the addition of camera cages for enhanced camera protection.

## Warranty Agreement

Safety Vision's standard warranty for new items is one year. Extended warranties and advance replacement agreements also are available. Ask your sales or customer service representative for details.



### CORPORATE HEADQUARTERS

6100 W. Sam Houston Pkwy. N.  
Houston, TX 77041  
U.S.A.  
Tel: 713.896.6600  
Toll Free: 800.880.8855

[www.safetyvision.com](http://www.safetyvision.com)

**SAFETY  
VISION®**

*Mobile video solutions for enhanced safety*